



Evaluation Listing CCMC 14034-L Styrobar® HS-40

MasterFormat:	07 21 13.06
Evaluation issued:	2016-04-14
Re-evaluation due:	2019-04-14

1. Evaluation

The product conforms to CAN/ULC-S701-11. The evaluation of this product is based solely on its certification and listing by QAI Laboratories Ltd.

Styrobar® HS-40 products are molded at minimum 38 kg/m³ density. As such, these products are not classified for surface burning characteristics noted and are not considered eligible for use as interior insulation products.

2. Description

Styrobar® HS-40 is rigid insulation made from Type 3 expanded polystyrene (EPS). Styrobar® HS-40 is available in all standard sizes starting at 50 mm (1/2") thick to 300 mm (12") thick, in 1200 mm x 2 400 mm (4' x 8') or 600 mm x 2 400 mm (2' x 8') sheets. Custom thickness up to 925 mm (37") are available on a special order basis. Styrobar® HS-40 is available with either a butt edge or shiplap edge.

3. Standard and Regulatory Information

See the Annex, appended to this Listing, which summarizes the product standard.

This/these product(s) was/were evaluated to the product standard referenced in the Annex current as of 2012-03-05. Note that the Annex may have been updated since this Listing was issued to include more recent editions of the applicable product standard. Therefore, this Listing may not reflect the requirements contained in any updated version of this product standard.

Listing Holder

AMC Foam Technologies Inc.
35 Headingley Street
Headingley, MB R4H 0A8

Telephone: 604-874-9926

Fax: 604-874-0153

Email: info@amcfoam.com

Web: www.amcfoam.com

Plant(s)

Headingley, MB

Disclaimer

This Listing is issued by the Canadian Construction Materials Centre, a program of NRC Construction at the National Research Council of Canada. The Listing must be read in the context of the entire CCMC Registry of Product Evaluations.

Readers must confirm that the Listing is current and has not been withdrawn or superseded by a later issue. Please refer to http://www.nrc-cnrc.gc.ca/eng/solutions/advisory/ccmc_index.html, or contact the Canadian Construction Materials Centre, NRC Construction, National Research Council of Canada, 1200 Montreal Road, Ottawa, Ontario, K1A 0R6. Telephone (613) 993-6189. Fax (613) 952-0268.

NRC has evaluated the material, product, system or service described herein only for those characteristics stated herein. The information and opinions in this Listing are directed to those who have the appropriate degree of experience to use and apply its contents. This Listing is provided without representation, warranty, or guarantee of any kind, expressed, or implied, and the National Research Council of Canada (NRC) provides no endorsement for any evaluated material, product, system or service described herein. NRC accepts no responsibility whatsoever arising in any way from any and all use and reliance on the information contained in this Listing. NRC is not undertaking to render professional or other services on behalf of any person or entity nor to perform any duty owed by any person or entity to another person or entity.

Date modified:
2016-05-31